

Fixed Speed Belt Drive Series

Oil – injected Rotary Screw Air Compressor

MODEL	WORKING PRESSURE		CAPACITY		POWER TRANSMISSION TYPE	Motor power		connection size		Dimension			WEIGHT	NOISE
	bar	psi	m3/min	cfm		kw	HP	Inch	DN	Length	Width	Height	Kg	dB(A)
RSB-10	7.5	110	1.35	48	BELT	7.5	10	1	25	1100	800	1250	185	69 ± 2
	8.5	120	1.2	42										
	10	145	1	35										
	13	190	0.8	28										
RSB-15	7.5	108	1.8	64	BELT	11	15	1	25	1100	800	1250	255	70 ± 2
	8.5	120	1.6	56										
	10	145	1.3	46										
	13	190	1	35										
RSB-20	7.5	110	2.5	88	BELT	15	20	1	25	1200	850	1250	285	85 ± 2
	8.5	120	2.3	81										
	10	145	2	71										
	13	190	1.7	60										
RSB-25	7.5	110	3	106	BELT	19	25	1	25	1200	850	1250	460	70 ± 2
	8.5	120	2.8	99										
	10	145	2.5	88										
	13	190	2	71										
RSB-30	7.5	110	3.8	134	BELT	22	30	1	25	1350	1000	1350	470	70 ± 2
	8.5	120	3.4	120										
	10	145	3.1	109										
	13	190	2.7	95										
RSB-40	7.5	110	5.2	183	BELT	30	40	1.1/2	32	1450	1000	1450	550	75 ± 2
	8.5	120	5	176										
	10	145	4.3	152										
	13	190	3.8	134										
RSB-50	7.5	110	6.5	229	BELT	37	50	1.1/2	32	1550	1100	1550	950	73 ± 2
	8.5	120	6.1	215										
	10	145	5.5	194										
	13	190	4.9	173										
RSB-60	7.5	110	8	282	BELT	45	60	1.1/2	32	1800	1150	1800	1350	73 ± 2
	8.5	120	7.8	275										
	10	145	7	247										
	13	190	6	212										
RSB-75	7.5	110	10.5	370	BELT	55	75	1.1/2	32	1800	1100	1800	1550	73 ± 2
	8.5	120	9.8	346										
	10	145	8.9	314										
	13	190	7.6	268										
RSB-100	7.5	110	14.1	497	BELT	75	100	2	50	1900	1100	1900	2550	75 ± 2
	8.5	120	12.8	452										
	10	145	11.6	409										
	13	190	10	353										

NOTE :

Only Air-cooled versions are available