

Variable Speed Drive Series

Oil – injected Rotary **Screw** Air Compressor

MODEL	Rang WORKING PRESSURE				CAPACITY				POWER TRANSMISSION TYPE	Motor power		connesction size		Dimensions			WEIGHT	NOISE
	Minimum		Maximum		Minimum		Maximum			KW	HP	Inch	DN	Length	Width	Height	Kg	dB(A)
	bar	psig	bar	psig	m3/min	cfm	m3/min	cfm										
RSV-50	4.5	65	13	190	4.6	162	7.5	265	Direct	37	50	1.1/4	32	1650	1200	1800	1100	73 ± 2
RSV-60	4.5	65	13	190	5.6	198	8.8	311	Direct	45	60	1.1/2	40	1650	1200	1800	1350	73 ± 2
RSV-75	4.5	65	13	190	6.5	230	11	388	Direct	55	75	1.1/2	40	2000	1150	1840	1550	73 ± 2
RSV-100	4.5	65	13	190	9.5	335	15.5	547	Direct	75	100	2	50	2300	1300	1840	2550	75 ± 2
RSV-125	4.5	65	13	190	11.6	409	17	600	Direct	90	125	2	50	2300	1300	1840	2950	75 ± 2
RSV-150	4.5	65	13	190	14	494	19	671	Direct	110	150	2	50	2800	1600	1840	2950	75 ± 2
RSV-180	4.5	65	13	190	20	706	24	847	Direct	132	180	3	80	3000	1700	2070	3000	77 ± 2
RSV-220	4.5	65	13	190	19.8	699	27.5	971	Direct	160	220	3	80	3000	1700	2070	3400	78 ± 2
RSV-270	4.5	65	13	190	24.5	865	44	1554	Direct	200	270	4	100	3000	1700	2070	4500	75 ± 2
RSV-340	4.5	65	13	190	32	1130	52	1836	Direct	250	340	4	100	4000	2500	2070	5950	75 ± 2
RSV-400	4.5	65	13	190	39	1377	54	1907	Direct	315	400	4	100	4000	2500	2070	6700	75 ± 2

NOTE :

Both Air-cooled and Water-cooled versions are available